
Revision: 05.12.2018



Revision: 05.12.2018

Trade name: TC6046 SCREENWASH 4001

(Contd. of page 1)
yclohexanone
lazard statements
I226 Flammable liquid and vapour.
1332 Harmful if inhaled.
1335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
1304 May be fatal if swallowed and enters airways.
I411 Toxic to aquatic life with long lasting effects.
Precautionary statements
2210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
Do NOT induce vomiting.
2303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin
with water/shower.
2405 Store locked up.
2501 Dispose of contents/container in accordance with local/regional/national/
international regulations.
.3 Other hazards
Results of PBT and vPvB assessment
PBT: Not applicable.

• **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous compone	ents:	
	Solvent naphtha (petroleum), light arom.	25-50%
EINECS: 265-199-0	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Acute Tox. 4, H332; STOT SE 3, H335	
CAS: 107-98-2	1-methoxy-2-propanol	10-25%
EINECS: 203-539-1	🚸 Flam. Liq. 3, H226; 🚸 Acute Tox. 3, H331; 🚯 STOT SE 3, H336	
CAS: 108-94-1	cyclohexanone	10-25%
EINECS: 203-631-1	🚸 Flam. Liq. 3, H226; 🚸 Acute Tox. 4, H332	
Additional information: For the wording of the listed hazard phrases refer to section 16.		

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.

(Contd. on page 3)

⁻ GB

Revision: 05.12.2018

(Contd. of page 2)

Trade name: TC6046 SCREENWASH 4001

• After swallowing: If symptoms persist consult doctor.

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions:
- Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- \cdot 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

(Contd. on page 4)

Revision: 05.12.2018

(Contd. of page 3)

Trade name: TC6046 SCREENWASH 4001

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk

108-94-1 cyclohexanone

WEL Short-term value: 20 ppm Long-term value: 10 ppm Sk

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

• Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Plastic gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- \cdot Not suitable are gloves made of the following materials:
- PVC gloves

Synthetic rubber gloves Leather gloves

Strong material gloves

(Contd. on page 5)

Revision: 05.12.2018

Trade name: TC6046 SCREENWASH 4001

(Contd. of page 4) · Eye protection: Tightly sealed goggles **SECTION 9: Physical and chemical properties** · 9.1 Information on basic physical and chemical properties · General Information · Appearance: Form: Fluid Colour: According to product specification · Odour: Characteristic · Odour threshold: Not determined. Not determined. · pH-value: · Change in condition Undetermined. *Melting point/freezing point:* Initial boiling point and boiling range: 120 °C 35 °C · Flash point: 270 °C · Ignition temperature: Not determined. · Decomposition temperature: • Auto-ignition temperature: Product is not selfigniting. Product is not explosive. However, formation of explosive air/ • Explosive properties: vapour mixtures are possible. · Explosion limits: 0.7 Vol % Lower: Upper: 9.4 Vol % · Vapour pressure at 20 °C: 12 hPa • Density at 20 •C: 0.913 g/cm³ · Relative density Not determined. · Vapour density Not determined. Not determined. · Evaporation rate · Solubility in / Miscibility with water: Not miscible or difficult to mix. Not determined. · Partition coefficient: n-octanol/water: · Viscosity: Dvnamic: Not determined. Kinematic: Not determined. · Solvent content: 100.0 % Organic solvents: 100.00 % VOC (EC)

(Contd. on page 6)

- GB

Revision: 05.12.2018

(Contd. of page 5)

Trade name: TC6046 SCREENWASH 4001

• 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Harmful if inhaled.

· LD/LC50 values relevant for classification:

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (rat)
	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

108-94-1 cyclohexanone

Oral	LD50	1535 mg/kg (rat)
Dermal	LD50	948 mg/kg (rabbit)
Inhalative	LC50/4 h	8000 mg/l (rat)

• Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause respiratory irritation. May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard
- May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.

(Contd. on page 7)

Revision: 05.12.2018

(Contd. of page 6)

Trade name: TC6046 SCREENWASH 4001

- **12.2 Persistence and degradability** No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- **Remark:** Toxic for fish
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms

· 12.5 Results of PBT and vPvB assessment

- *PBT:* Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR, IMDG, IATA	1993
· 14.2 UN proper shipping name	
ADR	1993 FLAMMABLE LIQUID, N.O.S. (1-METHOXY-2 PROPANOL, Solvent naphtha (petroleum), ligh arom.)
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (1-METHOXY-2 PROPANOL, Solvent naphtha (petroleum), ligh arom.)
· 14.3 Transport hazard class(es)	
ADR, IMDG	
· Class	3 Flammable liquids.

Revision: 05.12.2018

Trade name:	TC6046	SCREENWASH	4001

	(Contd. of page
Label	3
IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	Yes
	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
EMS Number:	F- E , S - E
14.7 Transport in bulk according to Ann	ex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	LQ7
Transport category	3
Tunnel restriction code	D/E
UN "Model Regulation":	UN1993, FLAMMABLE LIQUID, N.O.S., 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture • Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms GHS02, GHS07, GHS08, GHS09
- · Signal word Danger
- · Hazard-determining components of labelling:
- Solvent naphtha (petroleum), light arom.
- *1-methoxy-2-propanol* cyclohexanone

· Hazard statements

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

- H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
- H304 May be fatal if swallowed and enters airways.
- *H411 Toxic to aquatic life with long lasting effects.*

(Contd. on page 9)

GB

Revision: 05.12.2018

Trade name: TC6046 SCREENWASH 4001

	(Contd. of page 8)
· Precautionary stat	ements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
	No smoking.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331	Do NOT induce vomiting.
P303+P361+P353	B IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin
	with water/shower.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/
	international regulations.
· REGULATION (E	C) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H331 Toxic if inhaled. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: product safety department

· Contact: Mr L Cooper

· Abbreviations and acronvms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organisation ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO) ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity - Category 4 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

GR