
Revision: 05.12.2018



Revision: 05.12.2018

Trade name: TC6024 SCREEN WASH 4007

	(Contd. of page 1)
Hazard-determi	ining components of labelling:
Solvent naphtha	(petroleum), light arom.
1-methoxy-2-pro	opanol
cyclohexanone	•
Hazard stateme	nts
H226 Flammabi	le liquid and vapour.
H332 Harmful ij	f inhaled.
H319 Causes se	rious eye irritation.
H335 May cause	e respiratory irritation.
H304 May be fa	tal if swallowed and enters airways.
H411 Toxic to a	quatic life with long lasting effects.
Precautionary s	tatements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
	No smoking.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331	Do NOT induce vomiting.
P303+P361+P3	353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin
	with water/shower.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/
2204	international regulations.
2.3 Other hazar	
	and vPvB assessment
PBT: Not applie	

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous compone	ents:	
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	50-100%
EINECS: 265-199-0	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Acute Tox. 4, H332; STOT SE 3, H335	
CAS: 107-98-2	1-methoxy-2-propanol	2.5-10%
EINECS: 203-539-1	🚸 Flam. Liq. 3, H226; ⊗ Acute Tox. 3, H331; 🚯 STOT SE 3, H336	
	4-hydroxy-4-methylpentan-2-one	2.5-10%
EINECS: 204-626-7	🚸 Flam. Liq. 3, H226; 🚸 Eye Irrit. 2, H319	
CAS: 108-94-1	cyclohexanone	2.5-10%
EINECS: 203-631-1	🚸 Flam. Liq. 3, H226; 🚯 Acute Tox. 4, H332	
· Additional informati	on: For the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.

(Contd. on page 3)

GB

Revision: 05.12.2018

Trade name: TC6024 SCREEN WASH 4007

(Contd. of page 2)

- After eye contact:
- *Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.* • *After swallowing: If symptoms persist consult doctor.*
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

(Contd. on page 4)

GR

Revision: 05.12.2018

(Contd. of page 3)

Trade name: TC6024 SCREEN WASH 4007

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

·	8.1	Control	parameters
---	-----	---------	------------

· Ingredients with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk

123-42-2 4-hydroxy-4-methylpentan-2-one

WEL Short-term value: 362 mg/m³, 75 ppm Long-term value: 241 mg/m³, 50 ppm

108-94-1 cyclohexanone

WEL Short-term value: 20 ppm Long-term value: 10 ppm Sk

64742-95-6 Solvent naphtha (petroleum), light arom.

OEL Short-term value: 25 ppm RECOMMENDED

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes. Avoid contact with the eyes and skin.

• Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

Plastic gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)


GB

Revision: 05.12.2018

Trade name: TC6024 SCREEN WASH 4007

(Contd. of page 4)

- · Penetration time of glove material
- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Not suitable are gloves made of the following materials: Strong material gloves Leather gloves
- Eye protection:



9.1 Information on basic physical and c	hemical properties
General Information	
Appearance:	
Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: Undetermined.
Flash point:	37 °C
Ignition temperature:	270 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
Explosion limits:	
Lower:	0.7 Vol %
Upper:	9.4 Vol %
Vapour pressure at 20 °C:	12 hPa
Density at 20 °C:	0.8932 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.

Revision: 05.12.2018

(Contd. of page 5)

	Trade name: TC6024 SCREE	N WASH 4007	
ſ			
	· Viscosity:		
	Dynamic:	Not determined.	
	Kinematic:	Not determined.	

 Solvent content: Organic solvents: VOC (EC)
 9.2 Other information

100.0 % 100.00 % No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• *Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.*

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity

Harmful if inhaled.

· LD/LC50 values relevant for classification:

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (rat)
		>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

[·] Primary irritant effect:

- · Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause respiratory irritation.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard
- May be fatal if swallowed and enters airways.

(Contd. on page 7)

[·] Skin corrosion/irritation Based on available data, the classification criteria are not met.

Revision: 05.12.2018

Trade name: TC6024 SCREEN WASH 4007

(Contd. of page 6)

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:
- Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.
- Toxic for aquatic organisms
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	1263	
14.2 UN proper shipping name		
ADR	1263 PAINT RELATED MATERIAL	
IMDG, IATA	PAINT RELATED MATERIAL	
14.3 Transport hazard class(es) ADR, IMDG		
Class	3 Flammable liquids.	

Revision: 05.12.2018

Trade name: TC6024 SCREEN WASH 4007

	(Contd. of page
Label	3
IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	111
14.5 Environmental hazards:	Product contains environmentally hazardou
	substances: Solvent naphtha (petroleum), light arom.
Marine pollutant:	No
	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
EMS Number:	F-E,S-E
14.7 Transport in bulk according to Ann	ex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	LQ7
Transport category	3
Tunnel restriction code	D/E
UN ''Model Regulation'':	UN1263, PAINT RELATED MATERIAL, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture · Labelling according to Regulation (EC) No 1272/2008

- The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS02, GHS07, GHS08, GHS09
- · Signal word Danger
- · Hazard-determining components of labelling: Solvent naphtha (petroleum), light arom. 1-methoxy-2-propanol cyclohexanone · Hazard statements H226 Flammable liquid and vapour. H332 Harmful if inhaled.

H319 Causes serious eye irritation. H335 May cause respiratory irritation. H304 May be fatal if swallowed and enters airways.

(Contd. on page 9)

GB

GB

Safety data sheet according to 1907/2006/EC, Article 31

Revision: 05.12.2018

Trade name: TC6024 SCREEN WASH 4007

	(Contd. of page 8)
H411 Toxic to aqu	atic life with long lasting effects.
· Precautionary stat	tements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
	No smoking.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331	Do NOT induce vomiting.
P303+P361+P35.	3 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin
	with water/shower.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/
	international regulations.
· REGULATION (I	EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: product safety department

· Contact: Mr L Cooper

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organisation ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO) ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 3: Acute toxicity - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2