Revision: 06.12.2018

1.1 Product ide	ntifier	
Trade name: <u>T</u>	C 4001 VINYL	THINNER
No further relev	ant information	the substance or mixture and uses advised against a available. the mixture Thinner, Diluent
1.3 Details of th	e supplier of th	he safety data sheet
Further information product safety d THANET COAT 4 PATRICIA WA BROADSTAIRS 1.4 Emergency THANET COAT	epartment INGS LTD Y, PYSONS RC , KENT CT10 2 telephone num	DAD IND EST PLF sber:
THANET COAT	INGS LTD (44)) 01843 861861 DURING NORMAL OPENING TIMES
		unce or mixture gulation (EC) No 1272/2008
Classification a	ccording to Re 02 flame	
Classification a GHSC Flam. Liq. 3	ccording to Re 02 flame	gulation (EC) No 1272/2008 Flammable liquid and vapour.
Classification a GHSC Flam. Liq. 3	ccording to Reg 02 flame H226	gulation (EC) No 1272/2008 Flammable liquid and vapour.
Flam. Liq. 3 Flam. Liq. 3 GHS0 Asp. Tox. 1	ccording to Rey 02 flame H226 08 health hazar	gulation (EC) No 1272/2008 Flammable liquid and vapour. d May be fatal if swallowed and enters airways.
Classification a GHSC Flam. Liq. 3 GHSC Asp. Tox. 1	ccording to Rey D2 flame H226 D8 health hazar H304 D9 environment	gulation (EC) No 1272/2008 Flammable liquid and vapour. d May be fatal if swallowed and enters airways.
Classification a GHSC Flam. Liq. 3 GHSC Asp. Tox. 1 GHSC	ccording to Rey D2 flame H226 D8 health hazar H304 D9 environment c 2 H411	gulation (EC) No 1272/2008 Flammable liquid and vapour. d May be fatal if swallowed and enters airways.
Classification a GHSC Flam. Liq. 3 GHSC Asp. Tox. 1 GHSC Aquatic Chronic	ccording to Rey D2 flame H226 D8 health hazar H304 D9 environment c 2 H411	gulation (EC) No 1272/2008 Flammable liquid and vapour. d May be fatal if swallowed and enters airways.
Classification a GHSC Flam. Liq. 3 GHSC Asp. Tox. 1 Chronic Aquatic Chronic GHSC	ccording to Reg 02 flame H226 08 health hazar H304 09 environment 2 H411 07 H332	gulation (EC) No 1272/2008 Flammable liquid and vapour. d May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

Revision: 06.12.2018

Trade name: TC 4001 VINYL THINNER

components of labelling: pleum), light arom. l le liquid and vapour. f inhaled.
le liquid and vapour.
le liquid and vapour.
f inhaled.
e respiratory irritation. May cause drowsiness or dizziness.
tal if swallowed and enters airways.
equatic life with long lasting effects.
ents
pep away from heat, hot surfaces, sparks, open flames and other ignition sources.
o smoking.
SWALLOWED: Immediately call a POISON CENTER/ doctor.
o NOT induce vomiting.
ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin th water/shower.
ore locked up.
spose of contents/container in accordance with local/regional/national/ ternational regulations.
ore sp

- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

Dungerous compone	1113.	
		25-50%
EINECS: 265-199-0	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Acute Tox. 4, H332; STOT SE 3, H335	
CAS: 107-98-2	1-methoxy-2-propanol	10-25%
EINECS: 203-539-1	🚸 Flam. Liq. 3, H226; 🔗 Acute Tox. 3, H331; 🚯 STOT SE 3, H336	
	cyclohexanone	10-25%
EINECS: 203-631-1	🚸 Flam. Liq. 3, H226; 🚸 Acute Tox. 4, H332	
A 111/1 1 1 C		

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 3)

GB

Revision: 06.12.2018

Trade name: TC 4001 VINYL THINNER

(Contd. of page 2)

- After inhalation:
- Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** *No further relevant information available.*

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*

(Contd. on page 4)

Revision: 06.12.2018

Trade name: TC 4001 VINYL THINNER

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol

WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk

108-94-1 cyclohexanone

WEL Short-term value: 20 ppm Long-term value: 10 ppm Sk

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.
- · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Plastic gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- · Penetration time of glove material
- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Not suitable are gloves made of the following materials: PVC gloves

(Contd. on page 5)

Revision: 06.12.2018

Trade name: TC 4001 VINYL THINNER

(Contd. of page 4)

Synthetic rubber gloves Leather gloves Strong material gloves • **Eye protection:**



Tightly sealed goggles

9.1 Information on basic physical and c	hemical properties
General Information	
Appearance:	
Form: Colour:	Fluid
Odour:	According to product specification Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
•	
Change in condition	Undetermined.
Melting point/freezing point: Initial boiling point and boiling range	
Flash point:	35 °C
Ignition temperature:	270 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive ai vapour mixtures are possible.
Explosion limits:	
Lower:	0.7 Vol %
Upper:	9.4 Vol %
Vapour pressure at 20 •C:	12 hPa
Density at 20 °C:	0.913 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

Revision: 06.12.2018

Trade name: TC 4001 VINYL THINNER

(Contd.	of	page	5)
(Comu.	01	pube	\mathcal{I}

· Solvent content:	
Organic solvents:	100.0 %
VOC (EC)	100.00 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity
- Harmful if inhaled.

· LD/LC50 values relevant for classification:

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

108-94-1 cyclohexanone

	-	
Oral	LD50	1535 mg/kg (rat)
	LD50	948 mg/kg (rabbit)
Inhalative	LC50/4 h	8000 mg/l (rat)

· Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

· Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

• STOT-repeated exposure Based on available data, the classification criteria are not met.

· Aspiration hazard

May be fatal if swallowed and enters airways.

(Contd. on page 7)

Revision: 06.12.2018

Trade name: TC 4001 VINYL THINNER

(Contd. of page 6)

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:
- Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.
- Toxic for aquatic organisms
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR, IMDG, IATA	1993
• 14.2 UN proper shipping name	
ADR	1993 FLAMMABLE LIQUID, N.O.S. (1-METHOXY-2
	PROPANOL, Solvent naphtha (petroleum), ligh arom.)
· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (1-METHOXY-2
,	PROPANOL, Solvent naphtha (petroleum), ligh
	arom.)

Revision: 06.12.2018

	(Contd. of pag
14.3 Transport hazard class(es)	
ADR	
Class	3 Flammable liquids.
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDĞ, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
EMS Number:	F-E,S-E
14.7 Transport in bulk according to Anna	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	LQ7
Transport category	3
Tunnel restriction code	D/E
UN ''Model Regulation'':	UN1993, FLAMMABLE LIQUID, N.O.S., 3, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture · Labelling according to Regulation (EC) No 1272/2008

- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms GHS02, GHS07, GHS08, GHS09

· Signal word Danger

• *Hazard-determining components of labelling:* Solvent naphtha (petroleum), light arom. 1-methoxy-2-propanol cyclohexanone

(Contd. on page 9)

⁻ GB

Revision: 06.12.2018

Trade name: TC 4001 VINYL THINNER

	(Contd. of page 8)
· Hazard stateme	nts
	mmable liquid and vapour.
	rmful if inhaled.
	y cause respiratory irritation. May cause drowsiness or dizziness.
	y be fatal if swallowed and enters airways.
	cic to aquatic life with long lasting effects.
• Precautionary s	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P301+P310 P331	IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Do NOT induce vomiting.
	0
	353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/
	international regulations.
· REGULATION	(EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
	safety assessment: A Chemical Safety Assessment has not been carried out.
SECTION 16	6: Other information
	n is based on our present knowledge. However, this shall not constitute a guarantee for duct features and shall not establish a legally valid contractual relationship.
· Relevant phrase	26
	le liquid and vapour.
	tal if swallowed and enters airways.
H331 Toxic if in	
H332 Harmful ij	
H335 May cause	e respiratory irritation.
H336 May cause	e drowsiness or dizziness.
H411 Toxic to a	quatic life with long lasting effects.
	uing SDS: product safety department
• Contact: Mr L C	
 Abbreviations a 	nd acronyms:
	ernational concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning
	ansport of Dangerous Goods by Rail)
	rous Goods Regulations by the "International Air Transport Association" (IATA)
	l Civil Aviation Organisation I Instructions by the "International Civil Aviation Organisation" (ICAO)
	ppéen sur le transport des marchandises dangereuses par Route (European Agreement concerning the
	age of Dangerous Goods by Road)
	Il Maritime Code for Dangerous Goods
	Air Transport Association
	monised System of Classification and Labelling of Chemicals
	Inventory of Existing Commercial Chemical Substances
	List of Notified Chemical Substances
	tracts Service (division of the American Chemical Society)
LC50: Lethal conce	unic Compounds (USA, EU) ntration 50 percent
LD50: Lethal dose,	
	paccumulative and Toxic
	nt and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 3: Acute toxicity – Category 3

(Contd. on page 10)

GB

Printing date 05.12.2018

Revision: 13.01.2014

Trade name: TC 4001 VINYL THINNER

(Contd. of page 9)

GB

Acute Tox. 4: Acute toxicity – Category 4 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Mr L Cooper